



**Manufacturers of
Professional Grade Cement &
Construction Products Since 1967**

8/01-1

PERMA TILE GROUT

NON-YELLOWING, FADE RESISTANT

DESCRIPTION:

PERMA TILE GROUT is a special blend of Portland cements, fortifiers and graded fillers.

PERMA TILE GROUT is suitable for all grouting applications in the areas of floor and wall tile, shower stalls, towel rack and soap dishes, sink tops and mosaic tile applications.

ADVANTAGES:

- Mix with water only
- Produces a strong and durable grout joint
- Remains chip, shrink, stain and water resistant
- Bright white, non-yellowing and fade resistant
- May be tinted to match tile

SPECIAL NOTES:

1. **PERMA TILE GROUT** should be cured by misting with water at least once in the first 24 hours.
2. Suitable for new or restoration work

SURFACE PREPARATION:

For new installations allow the tile to set for 18 to 24 hours prior to proceeding with grouting. Tile and grout joints should be clean and free from any dust or adhesive. For re-grouting of old joints you must remove all dead or unsound grout with a grout joint saw. Wipe the surface with a damp cloth to remove any dust or dried soap from the tile and joint areas. No priming is required.

MIXING:

Add clean water to a mixing pail and gradually add the **PERMA TILE GROUT** to the pail while mixing. Continue to mix and add grout until a soft paste consistency is achieved. Let stand for 15 minutes and then re-temper. A small amount of additional water may be needed.

APPLICATION:

Apply **PERMA TILE GROUT** with a rubber grout float held at a 30° angle. Work grout into the joints with strokes at 45° angle to the grout joints.

Work in material until all gaps and air pockets have been removed. Remove excess material with grout float and move onto an adjoining area. Work in small areas that can be completed in 15 to 20 minutes.

CLEANING:

Allow the **PERMA TILE GROUT** to firm up but do not allow to dry before sponging. To remove excess material use a damp sponge in a circular motion. Do not use excessive water. Keep sponge clean by frequently rinsing in a bucket of water.

Do not allow **PERMA TILE GROUT** to dry prior to cleaning with a damp sponge.

After 2 to 3 hours a white haze will form on the tiles. This haze can be removed with a nylon sponge and then the tiles can be polished with a clean cloth.

SHELF LIFE: When stored in original, un-opened container, one year. Rotate your stock.

PACKAGING:

PERMA TILE GROUT is supplied in 1 and 5-pound containers.

COVERAGE:

PERMA TILE GROUT will cover 12 to 16 ft² per 1 pound.

STORAGE CONDITIONS:

PERMA TILE GROUT must be stored between 50° F (10° C) and 95° F (35° C) in a dry area. Avoid high humidity.

PRECAUTIONS:

1. Dispose of waste materials in accordance with Federal, State and local regulations
2. The use of a dust mask, safety goggles and rubber gloves are recommended.
3. Caution: Contains Portland Cement which is highly caustic
4. In case of contact, flush eyes with water. Wash skin with soap and water. Consult a physician

GENERAL INFORMATION:

Please contact CGM, Inc. at any of the following numbers for customer service or technical assistance:

Voice: 215-638-400
Toll Free: 800-523-6570
Fax: 215-638-7949
e-mail:
Sales /Technical: ebrunner@cgmcement.com
bruby@cgmcement.com

Inside Sales: fkinney@cgmcement.com
On the web @ www.cgmbuildingproducts.com

WARRANTY:

CGM INC. warrants this product to be free of manufacturing defects. The sole responsibility and maximum liability of CGM under this warranty shall be at CGM's option, either (1) to replace the defective product in the form the product was purchased but not in the form the product was installed or used, or (2) to refund the purchase price of the product. In no event shall CGM be liable to the purchaser or to any third party for any loss or damage, of any type, including but not limited to incidental and/or consequential damage, resulting from the purchase or use of this product. In the event of any claim under this warranty, written notice must be given by registered mail.

This warranty is in lieu of all other warranties, expressed or implied, including but not limited to warranties of merchantability and fitness for a particular purpose. Information contained herein is for evaluation purposes only. While CGM believes this information to be true and accurate as of this printing of this material, CGM shall have no obligation to notify purchasers of any error which is subsequently discovered in this information. CGM reserves the right to modify or improve any of its products, at any time without prior notice.

