



Manufacturers of Professional Grade Cement & Construction Products Since 1967

MATERIAL SAFETY DATA SHEET PRO VOC CONCRETE CURE AND SEALER

Manufacturer's Name CGM, Inc.	Emergency Telephone Number 215-638-4400 OR 800-523-6570
Address: 1445 Ford Rd. Bensalem, Pa. 19020	Telephone Number for Information 215-638-4400
Prepared By: Fred Kinney	Date Prepared JANUARY 28, 2003
Signature:	Title: Director Technical Operations

SECTION II - HAZARD INGREDIENTS/IDENTITY INFORMATION

MATERIAL OR COMPONENT	CAS #	%	HAZARDOUS DATA
Acrylate Polymer	60381-61-5	14-30	N/A
Odorless Mineral Spirits	64742-88-7	6-14	TLV 100ppm
Water		80-56	N/A
VOC CONTENT 343 GRAMS/LITER			
Boiling Point 212 ° F (100° C)		Specific Gravity (H ₂ O = 1) 0.9784	
Vapor Pressure (mm Hg.) 2mm Hg		% Volatile by Volume: 86.0	
Vapor Density (AIR = 1) As water		Evaporation Rate As water (Butyl Acetate = 1)	
Solubility in Water: Complete Appearance and Odor: Milky white liquid with aromatic odor			

SECTION III - FIRE AND EXPLOSION HAZARD DATA

Flash Point: 194° F (90° C)	Unusual Fire & Explosion Hazard: None
Flammable Limits: None	Upper N/D Lower N/D
Extinguishing Media: Water and/or foam	Flammability: None
Autoignition Temperature: N/D	Special Fire Fighting Procedures: Fire fighters should wear self contained breathing apparatus to avoid inhalation of smoke and vapors.

SECTION IV – HEALTH HAZARD DATA

Route(s) of Entry: Yes	Inhalation Yes	Skin Yes	Eye: Yes
Health Hazards (Acute and Chronic) Contact with skin may cause dermatitis			
Symptoms of Exposure: Exposure to skin may cause rash and redness.			
Emergency First Aid: If ingested induce vomiting and seek immediate medical attention.			
Skin: Wash with soap and water		Eyes: Flush with copious amounts of clean water for 15 minutes	

SECTION V– EMERGENCY AND FIRST AID PROCEDURES

Emergency and First Aid Procedures:

Eyes: May cause slight irritation, irrigate eyes for at least 15 minutes with clean potable water.

Skin: Contact with skin may cause irritation and/or rash. Always wash exposed areas twice with soap and water. If irritation continues, seek medical attention.

Ingestion: Induce vomiting and seek immediate medical attention. Call the Poison Control Center in you area

SECTION VI – REACTIVITY DATA

Conditions Known to Cause Instability: Product is stable

Incompatibility/Materials to avoid: Strong acids will produce coagulation of solids/liquid

Hazardous Decomposition: None

SECTION VII – SPECIAL PROTECTION INFORMATION

Personal Protection Equipment: Neoprene gloves, goggles, impervious clothing and shoes.

Gloves: Neoprene gloves **Respirator:** A Organic Mist (Vapor)

Eyes: Chemical goggles **Footwear:** Imprevious

Clothing: Normal work clothes. Shirts with long sleeves are recommended.

Handling Procedures and Equipment: Material is very stable.

Engineering Controls: Normal mechanical ventilation and exhaust are preferred.

SECTION VIII – SPILL, LEAK AND DISPOSAL

Storage Requirements: Store in a well ventilated area. Keep away from high temperatures, open flames and sparks

Waste Disposal: Dispose of in accordance with Federal, State and Local regulations

Special Shipping Instructions.. If shipped in containers less than 119 gallons non-regulated material

The information provided in this Material Safety Data Sheet has been obtained from source(s) believed to be reliable. CGM, Inc. provides no warranties, express or implied and assumes no responsibility for the accuracy or completeness of the information contained herein.