



**Manufacturers of  
Professional Grade Cement &  
Construction Products Since 1967**

8/01-1

# PRO PERFECT PATCH

## POLYMER MODIFIED, CEMENTITIOUS PATCH

### DESCRIPTION:

**PRO PERFECT PATCH** is a polymer modified, cementitious patching material. **PRO PERFECT PATCH** is used for removing imperfections in cast in places, pre-cast and tilt wall concrete.

**PRO PERFECT PATCH** is applied to dry concrete and will fill bug holes and irregularities that would otherwise reflect through paint. **PRO PERFECT PATCH** will feather out and make the imperfections invisible after painting.

### ADVANTAGES:

- Excellent bond to existing substrate
- Capable of troweling to a feather edge
- Fills holes, cavities and cracks

### MIXING:

Mix **PRO PERFECT PATCH** with approximately 1 ½-2 gallons of water per 40 pound bag with a power drill and mixing paddle. Mix for at least 3 minutes at about 400 rpm. Mix only enough material that you can apply in 2 hours.

### APPLICATION:

After properly mixing a batch of **PRO PERFECT PATCH**, apply the material to the concrete surface with a hand trowel, applying pressure to the edge of the trowel to skim the material as thinly as possible over the surface.

When filling a void, you must pass the material over the void in multiple directions to achieve a completely filled void. The material will eventually become smooth after the sanding operation so it is not necessary to try and achieve this prior to the sanding.

Deeper holes in the surface should receive one heavy pass of the material and then let it set for approximately 30 minutes. Recoat the area. Proceed with this application method until the area to be patched is complete.

### FEATHERING INSTRUCTIONS:

After **PRO PERFECT PATCH** has been applied, let dry for approximately 2 hours, dependent on weather conditions. The material will be substantially lighter in color when dried.

Remove the edges and trowel marks by lightly sanding with 80 grit sand paper. If the material sets overnight or it rains, the trowel marks and edges can be removed by the use of a small angle grinder with an abrasive cup wheel. After sanding or grinding, the material should be allowed to set for no less than 48 hours, or have a pH insensitive primer applied prior to painting.

After proper curing and/or priming, the surface can be painted successfully. If properly applied and feathers, the **PRO PERFECT PATCH** will remove all imperfections from the concrete surface and produce a permanent finished drywall appearance.

**WORKING TIME:**

PRO PERFECT PATCH has a working time of 2 hrs. at 70° F (21° C).

**PACKAGING:** PRO PERFECT PATCH is available in a 40lb. bag.

**PRECAUTIONS:**

- Dispose of waste materials in accordance with Federal, State and local regulations.
- The use of a dust mask, safety goggles and rubber gloves are recommended.
- Contains Free Silica. Do not breath the dust as inhalation may cause delayed lung injury (silicosis) and is a carcinogen.
- In case of eye contact, flush with water. Wash skin with soap and water if contact occurs. Consult a Physician
- Use only with adequate ventilation

**KEEP OUT OF REACH OF CHILDREN**

**SHELF LIFE:**

When stored in original, un-opened container, one year. Rotate your stock.

**GENERAL INFORMATION:**

Please contact CGM, Inc. at any of the following numbers for customer service or technical assistance:

Voice: 215-638-4400  
Toll Free: 800-523-6570  
Fax: 215-638-7949  
E-mail:  
Sales /Technical: [ebrunner@cgmcement.com](mailto:ebrunner@cgmcement.com)  
[bruby@cgmcement.com](mailto:bruby@cgmcement.com)  
Technical: [fkinney@cgmcement.com](mailto:fkinney@cgmcement.com)  
Inside Sales: [ckuffman@cgmcement.com](mailto:ckuffman@cgmcement.com)  
On the web @: [www.cgmbuildingproducts.com](http://www.cgmbuildingproducts.com)

**WARRANTY:**

CGM INC. warrants this product to be free of manufacturing defects. The sole responsibility and maximum liability of CGM under this warranty shall be at CGM's option, either (1) to replace the defective product in the form the product was purchased but not in the form the product was installed or used, or (2) to refund the purchase price of the product. In no event shall CGM be liable to the purchaser or to any third party for any loss or damage, of any type, including but not limited to incidental and/or consequential damage, resulting from the purchase or use of this product. In the event of any claim under this warranty, written notice must be given by registered mail. This warranty is in lieu of all other warranties, expressed or implied, including but not limited to warranties of merchantability and fitness for a particular purpose. Information contained herein is for evaluation purposes only. While CGM believes this information to be true and accurate as of this printing of this material, CGM shall have no obligation to notify purchasers of any error which is subsequently discovered in this information. CGM reserves the right to modify or improve any of its products, at any time without prior notice.